

Model PSC

Car, Building Purpose High Performance Pressure Transducer

Description

PSC is compact size to vehicles and heavy machinery. It is also suitable for low pressure measurement and precise measurement. It builds an amplifier to interface with various kinds of controllers.

Features

- ▶ CE Certified
- ▶ VDC, mA output
- ▶ Measuring range 0~70MPa
- ▶ 0.25%FS accuracy
- ▶ IP65 protection(Head, DIN connector type)
IP55 protection(Cable type)
- ▶ Gauge and absolute measurement
- ▶ Piezoresistive silicon cell
- ▶ Stainless steel media-wetted materials

Applications

- ▶ Off road equipment
- ▶ Hydraulics & Pneumatic
- ▶ Compressor control
- ▶ Industrial engines
- ▶ Pump pressure control

Specifications



Range

0 ~ 5kPa ... 70MPa(Gauge)
-100kPa ~ 0 ... 70MPa (Gauge)
0 ~ 35kPa ... 70MPa (Absolute)

Performance

Accuracy	±0.25%FS(RSS)
Thermal Effect on Zero	±0.05%FS/°C
Thermal Effect on Span	±0.05%FS/°C
Compensated Temperature Range	-10 ~ 70°C
Operating Temperature Range	-20 ~ 100°C (Optional -30~120°C)

Electrical


Excitation	11 ~ 28VDC
Output	0~5VDC, 1~5VDC, 0~10VDC, 4~20mA(2Wire)
Electrical Connection	Connector, Cable, AMP Connector(1~5VDC 3Wire Only), Head, DIN Connector

Physical

Proof Pressure	X3 or 140MPa, Whichever is less.
Burst Pressure	X4 or 210MPa, Whichever is less.
Vibration	49.1m/s ² {5G}, 10~500Hz
Shock	490m/s ² {50G}
Pressure port	R(PT)1/8", G(PF)1/8", R(PT)1/4", G(PF)1/4", R(PT)3/8", G(PF)3/8"
Media-Wetted Materials	Stainless Steel 304, 316L, VITON
Weight	Approx. 130g (AMP Connector Type)


Dimension

► AMP Connector Type




Wire Color	Connections
Red	Input ⊕
White	Common ⊖
Green	Output ⊕

► Cable Type




Wire Color	Connections		
	4Wire	3Wire	2Wire
Red	Input ⊕	Input ⊕	Input ⊕
White	Output ⊖	Common ⊖	×
Black	Input ⊖	×	Output ⊕
Green	Output ⊕	Output ⊕	×
Shield	Earth	Earth	Earth

► Cable Gland Type




Wire Color	Connections		
	4Wire	3Wire	2Wire
Red	Input ⊕	Input ⊕	Input ⊕
White	Output ⊖	Common ⊖	×
Black	Input ⊖	×	Output ⊕
Green	Output ⊕	Output ⊕	×
Shield	Earth	Earth	Earth

► Connector Type




Pin No.	Wire Color	Connections		
		4Wire	3Wire	2Wire
1	Red	Input ⊕	Input ⊕	Input ⊕
2	White	Output ⊖	Common ⊖	×
3	Black	Input ⊖	×	Output ⊕
4	Green	Output ⊕	Output ⊕	×
5	Shield	Earth	Earth	Earth

► Head Type



No.	Connections	
	2Wire	
+	Input ⊕	
⊕	Earth	
-	Output ⊕	


► DIN connector Type




Pin No.	Connections	
	3Wire	2Wire
1	Input ⊕	Input ⊕
2	Common ⊖	Output ⊕
3	Output ⊕	×
⊕	Earth	Earth

Internal Circuit Diagram

► 2Wire mA Output Type



► 3, 4Wire mA, VDC Output Type



Ordering Information

Model Name		PSC E 0005 R A P G - □	Option
Output		B : 4Wire 0~5V H : 2Wire 4~20mA C : 3Wire 0~5V J : 3Wire 0~10V D : 4Wire 1~5V K : 4Wire 0~10V E : 3Wire 1~5V	B : Temperature Range -30~120°C Type of Pressure Measurement G : Gauge J : Absolute
Pressure Range		XXXX : Pressure CXXX : Compound Pressure	Connecting Methods
Pressure Unit		R : kPa M : MPa B : bar K : kgf/cm² P : psi H : mmHg C : cmH₂O	P : Connector C : Cable F : AMP Connector H : Head I : Din 43650-A connector S : Cable Gland
			Pressure port
			A : R(PT)3/8" D : G(PF)1/4" B : G(PF)3/8" G : R(PT)1/8" C : R(PT)1/4" H : G(PF)1/8"



SENSOR SYSTEM TECHNOLOGY CO., LTD.

ADD : Rm.5010, Ansan Digital Park, 81, Neungan-ro,
Danwon-gu, Ansan-si, Gyeonggi-do, Korea

TEL : +82-31-310-8910~9

FAX : +82-31-310-8920

http://www.sensys.co.kr

e-mail : master@sensys.co.kr

. Specifications are subject to change without notice.

© 2024. SENSOR SYSTEM TECHNOLOGY INC. all rights reserved. (20240702)